

IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the present application:

1-7. (Canceled)

8. (Previously presented) A method of generating an output image based on a first image and a second image, the method comprising:

- determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel;

- performing active display processing to generate the output image if the first display position is within the active display region of the display panel; and

- performing blanking processing to generate the output image if the first display position is not within the active display region of the display panel;

- wherein performing active display processing comprises:

- performing selective display processing if the first image and the second image are not both active at the first display position; and

- performing composite display processing if the first image and the second image are both active at the first display position;

- wherein performing composite display processing comprises:

- selecting, as the first pixel of the output image, either a first pixel of the first image, a first pixel of the second image, or a blending of the first pixel of the first image and the first pixel of the second image, based upon a processing control input, the

processing control input indicating whether the first image is transparent or opaque, whether the second image is transparent or opaque, and whether the first image is on top of the second image.

9. (Original) The method of claim 8 wherein the processing control input comprises a first control signal, the first control signal is set if the first image is transparent and not set if the first image is opaque, a second control signal, the second control signal is set if the second image is transparent and not set if the second image is opaque, and a third control signal, the third control signal is set if the first image is on top of the second image and not set if the second image is on top of the first image.

10. (Original) The method of claim 9 wherein the first pixel of the first image is selected as the first pixel of the output image if the first control signal is not set and the third control signal is set.

11. (Original) The method of claim 9 wherein the first pixel of the second image is selected as the first pixel of the output image if the second control signal is not set and third control signal is not set.

12. (Original) The method of claim 9 wherein the blending of the first pixel of the first image and the first pixel of the second image is selected as the first pixel of the output image if both the first control signal and the second control signal are set.

13. (Original) The method of claim 9 wherein the blending of the first pixel of the first image and the first pixel of the second image is selected as the first pixel of the output image if the first control signal is set and the third control signal is set.

14. (Original) The method of claim 9 wherein the blending of the first pixel of the first image and the first pixel of the second image is selected as the first pixel of the output image if the second control signal is set and the third control signal is not set.

15. (Original) The method of claim 8 wherein the blending of the first pixel of the first image and the first pixel of the second image is an alpha blending of the first pixel of the first image and the first pixel of the second image.

16. (Original) The method of claim 15 wherein the alpha blending comprises an alpha blending of a first component of the first pixel of the first image and a first component of the first pixel of the second image.

17. (Original) The method of claim 16 wherein the first component of the first pixel of the respective image is a chroma component indicative of a first characteristic of the first pixel or a luma component indicative of a second characteristic of the first pixel.

18. (Original) The method of claim 17 wherein the first characteristic is a color characteristic and the second characteristic is a brightness characteristic.

19. (Previously presented) A method of generating an output image based on a first image and a second image, the method comprising:

determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel;

performing active display processing to generate the output image if the first display position is within the active display region of the display panel; and

performing blanking processing to generate the output image if the first display position is not within the active display region of the display panel;

wherein the first image and the second image are selected from the group consisting of a digital video image, an analog video image, a graphics image, and a background color.

20. (Original) The method of claim 19 wherein the graphics image comprises a tiled graphics image.

21. (Original) The method of claim 19 wherein the graphics image comprises a cursor image.

22. (Previously presented) A method of generating an output image based on a first image and a second image, the method comprising:

determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel;

performing active display processing to generate the output image if the first display position is within the active display region of the display panel; and

performing blanking processing to generate the output image if the first display position is not within the active display region of the display panel;

wherein the output image is displayed on the display panel in an interlaced display mode.

23-24. (Canceled)

25. (Previously presented) A method of generating an output image based on a first image and a second image, the method comprising:

determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel;

performing active display processing to generate the output image if the first display position is within the active display region of the display panel; and

performing blanking processing to generate the output image if the first display position is not within the active display region of the display panel;

wherein determining whether the first display position is within the active display region comprises determining whether the display panel is in a blanking state, the first display position is within the active display region if the display panel is not in the blanking state;

wherein the display panel is in the blanking state if the display panel is in a horizontal blanking period.

26. (Canceled)

27. (Previously presented) A method of generating an output image based on a first image and a second image, the method comprising:

determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel;

performing active display processing to generate the output image if the first display position is within the active display region of the display panel; and

performing blanking processing to generate the output image if the first display position is not within the active display region of the display panel;

wherein performing blanking display processing comprises generating, based upon a blanking control input, either a blank signal, an end of active video (EAV) signal, a start of active video (SAV) signal, a constant value, a previous output pixel, or a pixel of ancillary data;

wherein the ancillary data is a text data, a video data, or a graphics data.

28-36. (Canceled)

37. (Previously presented) A method of composing an output image to be displayed on a display panel based upon multiple input images, the multiple input images comprising a first image, a second image, a third image and a fourth image, the method comprising:

determining whether the display panel is in a blanking display mode at a first display location on the display panel, the first display location corresponding to a location on the display panel where a first output pixel is to be displayed;

performing active display processing to compose the output image if the display panel is not in the blanking display mode; and

performing blanking display processing to compose the output image if the display panel is in the blanking display mode;

wherein the first image comprises a background image being selected from the group consisting of a background color image, a background tiled graphics image, and a background video image.

38. (Canceled)

39. (Original) The method of claim 37 wherein the second image comprises a video image.

40. (Original) The method of claim 37 wherein the third image comprises a graphics image.

41. (Original) The method of claim 37 wherein the fourth image comprises a cursor image.

42. (Original) The method of claim 37 wherein performing the active display processing comprises:

selecting as a first output data a first pixel of the second image if the second image is active at the first display location or the first pixel of the first image if the second image is not active at the first display location.

43. (Original) The method of claim 42 wherein the second image is active at the first display location if the first display location is within a second display area on the display panel that is to be occupied by the second image.

44. (Original) The method of claim 42 including:

blending a first pixel of the third image with the first output data to generate a second output data if the third image is active at the first display location and the third image is transparent.

45. (Original) The method of claim 44 including:

selecting as the second output data the first output data if the second image is active at the first display location and the second image is on top of the third image.

46. (Original) The method of claim 44 including:

selecting as the second output data the first pixel of the third image if the third image is active at the first display location and the third image is not transparent.

47. (Original) The method of claim 46 including:

blending a first pixel of the fourth image with the second output data to generate the first output pixel if the fourth image is active at the first display location and the fourth image is transparent;

selecting the first pixel of the fourth image as the first output pixel if the fourth image is active at the first display location and the fourth image is not transparent; and

selecting the second output data as the first output pixel if the fourth image is not active at the first display location.

48. (Original) The method of claim 37 wherein performing blanking display processing comprises:

generating blanking data selected from the group consisting of a blank signal, a constant value, a start of active video (SAV) signal, an end of active video (EAV) signal, a previous output pixel, and ancillary data.

49. (Original) The method of claim 48 wherein the ancillary data is selected from a text data, a video data, and a graphics data.

50-96. (Canceled)

97. (Currently amended) A method of generating an output image based on a plurality of images, including a first image and a second image, the method comprising:



receiving, at a display processing system, the plurality of images in a plurality of formats and from a plurality of sources, wherein the plurality of sources includes a video data source and a graphics data source; and

processing the plurality of images in said display processing system to generate the output image in response to a processing control input, wherein said processing control input is formulated based on determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel, wherein said processing includes

performing active display processing to generate the first pixel of the output image if the first display position is within the active display region of the display panel, wherein said active display processing includes

performing selective display processing if the first image and the second image are not both active at the first display position, and

performing composite display processing if the first image and the second image are both active at the first display position, wherein said composite display processing includes selecting, as the first pixel of the output image, either a first pixel of the first image, a first pixel of the second image, or a blending of the first pixel of the first image and the first pixel of the second image, based upon the processing control input, the processing control input indicating whether the first image is transparent or opaque, whether the second image is transparent or opaque, and whether the first image is on top of the second image; and

performing blanking processing to generate the first pixel of the output image if the first display position is not within the active display region of the display panel;

wherein the processing control input comprises a first control signal, the first control signal is set if the first image is transparent and not set if the first image is opaque, a second control signal, the second control signal is set if the second image is transparent and not set if the second image is opaque, and a third control signal, the

third control signal is set if the first image is on top of the second image and not set if the second image is on top of the first image.

98-100. (Canceled)

101. (Currently amended) The method of claim ~~400~~97, wherein the first image is active at the first display position if the first display position is within a first display area to be occupied by the first image and wherein the second image is active at the first display position if the first display position is within a second display area to be occupied by the second image.

102. (Currently amended) The method of claim ~~400~~97, wherein performing selective display processing comprises:

selecting, as the first pixel of the output image, either a first pixel of the first image if only the first image is active at the first display position or a first pixel of the second image if only the second image is active at the first display position.

103. (Previously presented) The method of claim 102, wherein the first pixel of the first image is a pixel of the first image whose display location corresponds to the first display position and wherein the first pixel of the second image is a pixel of the second image whose display location corresponds to the first display position.

104. (Currently amended) The method of claim ~~400~~97, wherein performing composite display processing comprises:

blending a first pixel of the first image with a first pixel of the second image to generate the first pixel of the output image.

105. (Previously presented) The method of claim 104, wherein the first pixel of the first image is a pixel of the first image whose display location corresponds to the first display position and wherein the first pixel of the second image is a pixel of the second image whose display location corresponds to the first display position.

106-107. (Canceled)

108. (Currently amended) The method of claim ~~407~~97, wherein the first pixel of the first image is selected as the first pixel of the output image if the first control signal is not set and the third control signal is set.

109. (Currently amended) The method of claim ~~407~~97, wherein the first pixel of the second image is selected as the first pixel of the output image if the second control signal is not set and third control signal is not set.

110. (Currently amended) The method of claim ~~407~~97, wherein the blending of the first pixel of the first image and the first pixel of the second image is selected as the first pixel of the output image if both the first control signal and the second control signal are set.

111. (Currently amended) The method of claim ~~407~~97, wherein the blending of the first pixel of the first image and the first pixel of the second image is selected as the first pixel of the output image if the first control signal is set and the third control signal is set.

112. (Currently amended) The method of claim ~~407~~97, wherein the blending of the first pixel of the first image and the first pixel of the second image is selected as the first

pixel of the output image if the second control signal is set and the third control signal is not set.

113. (Currently amended) The method of claim ~~406~~97, wherein the blending of the first pixel of the first image and the first pixel of the second image is an alpha blending of the first pixel of the first image and the first pixel of the second image.

114. (Previously presented) The method of claim 113, wherein the alpha blending comprises an alpha blending of a first component of the first pixel of the first image and a first component of the first pixel of the second image.

115. (Previously presented) The method of claim 114, wherein the first component of the first pixel of the respective image is a chroma component indicative of a first characteristic of the first pixel or a luma component indicative of a second characteristic of the first pixel.

116. (Previously presented) The method of claim 115, wherein the first characteristic is a color characteristic and the second characteristic is a brightness characteristic.

117. (Currently amended) ~~The method of claim 98, A method of generating an output image based on a plurality of images, including a first image and a second image, the method comprising:~~

receiving, at a display processing system, the plurality of images in a plurality of formats and from a plurality of sources, wherein the plurality of sources includes a video data source and a graphics data source; and

processing the plurality of images in said display processing system to generate the output image in response to a processing control input, wherein said processing

control input is formulated based on determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel, and wherein the first image and the second image are selected from the group consisting of a digital video image, an analog video image, a graphics image, and a background color.

118. (Previously presented) The method of claim 117, wherein the graphics image comprises a tiled graphics image.

119. (Previously presented) The method of claim 117, wherein the graphics image comprises a cursor image.

120. (Currently amended) ~~The method of claim 98,~~ A method of generating an output image based on a plurality of images, including a first image and a second image, the method comprising:

receiving, at a display processing system, the plurality of images in a plurality of formats and from a plurality of sources, wherein the plurality of sources includes a video data source and a graphics data source; and

processing the plurality of images in said display processing system to generate the output image in response to a processing control input, wherein said processing control input is formulated based on determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel, and wherein the output image is displayed on the display panel in an interlaced display mode.

121. (Currently amended) The method of claim 99Z, wherein determining whether the first display position is within the active display region comprises:

determining whether the display panel is in a blanking state, the first display position is within the active display region if the display panel is not in the blanking state.

122. (Previously presented) The method of claim 121, wherein the display panel is in the blanking state if the display panel is in a vertical blanking period.

123. (Currently amended) ~~The method of claim 121.~~ A method of generating an output image based on a plurality of images, including a first image and a second image, the method comprising:

receiving, at a display processing system, the plurality of images in a plurality of formats and from a plurality of sources, wherein the plurality of sources includes a video data source and a graphics data source; and

processing the plurality of images in said display processing system to generate the output image in response to a processing control input, wherein said processing control input is formulated based on determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel, including determining whether the display panel is in a blanking state, wherein the display panel is in the blanking state if the display panel is in a horizontal blanking period, where the first display position is within the active display region if the display panel is not in the blanking state, and wherein said processing includes

performing active display processing to generate the first pixel of the output image if the first display position is within the active display region of the display panel, and

performing blanking processing to generate the first pixel of the output image if the first display position is not within the active display region of the display panel.

124. (Currently amended) The method of claim ~~999~~7, wherein performing blanking display processing comprises:

generating, based upon a blanking control input, either a blank signal, an end of active video (EAV) signal, a start of active video (SAV) signal, a constant value, a previous output pixel, or a pixel of ancillary data.

125. (Currently amended) ~~The method of claim 124, A method of generating an output image based on a plurality of images, including a first image and a second image, the method comprising:~~

receiving, at a display processing system, the plurality of images in a plurality of formats and from a plurality of sources, wherein the plurality of sources includes a video data source and a graphics data source; and

processing the plurality of images in said display processing system to generate the output image in response to a processing control input, wherein said processing control input is formulated based on determining whether a first display position on a display panel at which a first pixel of the output image is to be displayed is within an active display region of the display panel, wherein said processing includes

performing active display processing to generate the first pixel of the output image if the first display position is within the active display region of the display panel, and

performing blanking processing to generate the first pixel of the output image if the first display position is not within the active display region of the display panel, wherein said blanking display processing includes generating, based upon a blanking control input, either a blank signal, an end of active video (EAV) signal, a start of active video (SAV) signal, a constant value, a previous output pixel, or a pixel of ancillary data, wherein the ancillary data is a text data, a video data, or a graphics data.

126. (Previously presented) The method of claim 97, wherein processing the plurality of images comprises blending the plurality of images in a predetermined order.

127. (Previously presented) The method of claim 97, wherein processing the plurality of images comprises selecting an image from the plurality of images based on a plurality of factors.

128-132. (Canceled)